

Price list of rapid deployment cameras PRO designed for city monitoring and City Guards/Police.

CAMSAT 2019

below prices anre netto and do not include VAT 23% tax  
valid since 01.04.2019

Group	Index	Model	Picture	Description and features	Technical parameters	Discount	Netto retail price
<b>iCAM-MobileHD II</b>							
<b>Rapid deployment 4G / LTE cameras recharged from STREET LIGHTING with 22Ah lithium battery and video recording for 30 days</b>							
<b>No PTZ camera - Main unit for any IP camera</b>							
iCAM	1070	<b>iCAM-MobileHD II BACK</b> (version 2019)  (compatible with Hikvision, Dahua,...)		<p>POWER SUPPLY: FROM 230V AC TWILIGHT POWER</p> <p><b>LTE rapid deployment video monitoring system powered at night with a lighting pole and internal video recording for 30 days - without an IP camera.</b></p> <p><b>Key features:</b></p> <ul style="list-style-type: none"> <li>* 4G / LTE - YES (2xSIM)</li> <li>* Battery - YES 22Ah (12-16h with camera up to 12W)</li> <li>* Video recording for 30 days</li> <li>* Automatic battery charging with 230V - YES</li> <li>* Mobility and quick slide assembly - YES</li> <li>* Compatible with cameras and NVR Hikvision / Dahua - YES</li> <li>* Camera - NO (mechanically adapted to mount almost any PTZ IP camera of such brands as: Dahua, Hikvision)</li> </ul>	<p><b>Technical parameters:</b> WiFi transmission 5GHz, 4G / LTE, SIM socket x 2 pcs, LAN port with PoE x 2 pcs, ext. video recording with low compression with high image quality (1TB memory / recording for 30 days), power supply: 230V AC, 12V, 24V DC, light Li-Ion 22 Ah battery with automatic charging eg from a lamp post, built-in battery charger - YES, mechanical adapter for mounting any PTZ IP camera Hikvision and Dahua, quick sliding assembly, transparent for connection between the camera and VMS, external IP66.</p> <p><b>New technical parameters in 2019 version:</b></p> <ul style="list-style-type: none"> <li>* Displaying information about: alarm event, battery status and voltage, charging, sabotage, GSM connection quality;</li> <li>* Possibility to install the option: "MASS EVENTS" - tools that help in the implementation of smooth LTE transmission surrounded by thousands of mobile phones, e.g. near festivals, demonstrations, sports events, etc.</li> </ul> <p><b>Camera parameters:</b> does not contain a camera. Use your own IP camera from any manufacturer.</p> <p><b>Working time on the battery:</b> depends on the power of the camera - up to 12-16 hours</p> <p><b>Includes:</b> iCAM-MobileHD II BACK, 1TB memory, antennas, quick assembly GE-Mobile II x 1 pcs., assembly accessories x 1 pc.</p> <p><b>Recommended accessories:</b> Mounting adapter for cameras: Bosch, Axis, Avigillion, Novus, UNV, IDIS, Flir, GANZ and others; mounting adapter for bullet cameras; LTE SIMcam card; RC remote control; GPS; iCAM-BOX transmission;</p> <p>In the case of delivery of an IP camera to CAMSAT, the product will be sent back fully operational and ready for work.</p>	iCAM	€ 4 600,00
<b>Full set - main unit with cameras</b>							
iCAM	1071	<b>iCAM-MobileHD II X25 IR150</b> (version 2019)  (with camera PTZ Dahua or Hikvision)		<p>POWER SUPPLY: FROM 230V AC TWILIGHT POWER</p> <p><b>LTE rapid deployment video monitoring system powered at night with a lighting pole</b></p> <p><b>Key features:</b></p> <ul style="list-style-type: none"> <li>* as in iCAM-MobileHD II BACK</li> <li>* Camera - YES (PTZ with zoom x25, IR 150 m)</li> </ul>	<p><b>Technical parameters:</b> Identical to the iCAM-MobileHD II BACK</p> <p><b>Camera parameters:</b> 2 Mpix 1080p, Day / Night, sensitivity: 0.005 Lux / F1.6 (color), 0.0005 Lux / F1.6 (B / W), optical zoom x25, IR illuminator for 150 m, h265+, lens: 4.8 - 120mm, AWB, AGC, ATW, BLC, HLC, EIS, 2D / 3D DNR, WDR 120dB, Rol, Defog, intelligent image analysis (IVS) functions: Auto Tracking, virtual line crossing, intrusion detection, face detection and the appearance / disappearance of the object.</p> <p><b>Observation range:</b> Event detection: from a distance of 1613 m, Observation: 646 m, Diagnosis: 323 m, Identification: 161 m</p> <p><b>Working time on the battery:</b> up to 12 hours or up to 24 hours with an additional iCAM-Battery230 module</p> <p><b>Includes:</b> iCAM-MobileHD II BACK, PTZ camera x 1 pcs, 1TB memory, antennas, GE-Mobile II quick assembly socket x 1 pcs, mounting accessories x 1 pc.</p>	iCAM	€ 5 267,00
iCAM	1072	<b>iCAM-MobileHD II X15 IR100</b>  (with camera PTZ Hikvision)		<p>POWER SUPPLY: FROM 230V AC TWILIGHT POWER</p> <p><b>LTE rapid deployment video monitoring system powered at night with a lighting pole</b></p> <p><b>Key features:</b></p> <ul style="list-style-type: none"> <li>* as in iCAM-MobileHD II BACK</li> <li>* Camera - YES (PTZ with zoom x15, IR 100 m)</li> </ul>	<p><b>Technical parameters:</b> Identical to the iCAM-MobileHD II BACK</p> <p><b>Camera parameters:</b> 2 Mpix 1080p, Day / Night, sensitivity: 0.005 Lux (color), 0.001 Lux (B / W), optical zoom x15, IR illuminator for 100 m, h265+, lens: 5 - 75 mm, AWB, ATW, AGC, BLC, HLC, EIS, WDR 120 dB, 3D DNR, ROI, Defog, functions of intelligent image analysis: virtual line crossing, intrusion and detection, object appearance / disappearance.</p> <p><b>Observation range:</b> Event detection: from a distance of 900 m, Observation: 380 m, Diagnosis: 180 m, Identification: 90 m.</p> <p><b>Working time on the battery:</b> up to 12 hours or up to 24 hours with an additional iCAM-Battery230 module</p> <p><b>Includes:</b> iCAM-MobileHD II BACK, Hikvision camera x 1 pcs, 1TB memory, antennas, GE-Mobile II quick assembly socket x 1 pcs, assembly accessories x 1 pc.</p>	iCAM	€ 4 967,00

Price list of rapid deployment cameras PRO designed for city monitoring and City Guards/Police.

CAMSAT 2019

below prices anre netto and do not include VAT 23% tax valid since 01.04.2019

Group	Index	Model	Picture	Description and features	Technical parameters	Discount	Netto retail price
<b>iCAM-MiniHD II</b>							
<b>Rapid deployment cameras powered with 230V AC and with emergency buffer power supply for up to 4h</b>							
<b>No camera - Main unit for any IP camera</b>							
iCAM	1090	<b>iCAM-MiniHD II BACK</b> (compatible with Hikvision, Dahua,...)		<p>POWER SUPPLY: WITH CONTINUOUS 230V AC POWER</p> <p><b>LTE rapid deployment video monitoring system with 230V emergency power supply for 4h - without an IP camera.</b></p> <p><b>Key features:</b></p> <ul style="list-style-type: none"> <li>* 4G / LTE - YES (2xSIM)</li> <li>* Battery - YES (4h)</li> <li>* Automatic battery charging with 230V - YES</li> <li>* Mobility and quick slide assembly - YES</li> <li>* Compatible with cameras and NVR Hikvision / Dahua - YES</li> <li>* Camera - NO (mechanically adapted to mount almost any PTZ IP camera of such brands as: Dahua, Hikvision ...)</li> </ul>	<p><b>The most important parameters:</b> 4G / LTE transmission, 2x SIM socket, 2x LAN port with PoE, 230V AC power supply, emergency power backup for 4h, mechanical adapter for attaching Dahua and Hikvision PTZ suspended camera, fast pole / wall mounting socket, IP66, no contains cameras.</p> <p><b>New parameters for version 2019:</b></p> <ul style="list-style-type: none"> <li>* The possibility of displaying in the OSD video image information about: alarm event, battery status and voltage, charging, sabotage, GSM connection quality;</li> <li>* Possibility to install the option: "MASS EVENTS" - a tool that helps to make a smooth LTE transmission surrounded by thousands of mobile phones, eg near festivals, demonstrations, sports events, etc.</li> </ul> <p><b>Camera parameters:</b> does not contain a camera. Apply your own IP camera of any brand.</p> <p><b>Includes:</b> iCAM-MiniHD II BACK, antenna, quick assembly GE-Mobile II x 1 pcs. Assembly accessories x 1 pc.</p> <p><b>Recommended accessories:</b> Mounting adapter for cameras: Bosch, Axis, Avigillion, Novus, UNV, IDIS, Flir, GANZ and others; mounting adapter for bullet cameras; LTE SIMcam card; remote controller; GPS; iCAM-BOX transmission; Wi-Fi;</p> <p>In the case of delivery of an IP camera to CAMSAT, the product will be sent back fully operational and ready for work.</p>	iCAM	€ 1 593,00
<b>Full set - main unit with cameras</b>							
iCAM	1091	<b>iCAM-MiniHD II X4 LTE</b> (with camera PTZ Hikvision)		<p>POWER SUPPLY: WITH CONTINUOUS 230V AC POWER</p> <p><b>LTE rapid deployment video monitoring system with 230V emergency power supply for 4h</b></p> <p><b>Key features:</b></p> <ul style="list-style-type: none"> <li>* as in iCAM-MiniHD II BACK</li> <li>* Camera - YES (PTZ with zoom x4)</li> <li>* Video recording for 7-10 days</li> </ul>	<p><b>Technical parameters:</b> Identical to the iCAM-MiniHD II BACK</p> <p><b>Camera parameters:</b> 2 Mpix 1080p, Day / Night, sensitivity: 0.05 Lux / F1.6 (color), 0.01 Lux / F1.6 (B / W), optical zoom x4, IR illuminator - NO, H264, lens adjustable: 2.8 - 12 mm motozoom, AWB, ATW, AGC, BLC, HLC, 3D DNR, DWDR,</p> <p><b>Observation range:</b> Events detection: From distance: 110 m, Observation: 45 m, Diagnosis: 22 m, Identification: 10 m.</p> <p><b>Working time on the battery:</b> up to 10h</p> <p><b>Includes:</b> iCAM-MiniHD II BACK, Hikvision camera x 1 pcs, SD128GB memory x 1 pcs, antennas, GE-Mobile II quick assembly socket x 1 pcs, mounting accessories x 1 pc.</p>	iCAM	€ 2 063,00
iCAM	1092	<b>iCAM-MiniHD II X25 LTE</b> (with camera PTZ Dahua or Hikvision)		<p>POWER SUPPLY: WITH CONTINUOUS 230V AC POWER</p> <p><b>LTE rapid deployment video monitoring system with 230V emergency power supply for 4h</b></p> <p><b>Key features:</b></p> <ul style="list-style-type: none"> <li>* as in iCAM-MiniHD II BACK</li> <li>* Camera - YES (PTZ, zoom x25, IR 150 m)</li> <li>* Video recording for 7-10 days</li> </ul>	<p><b>Technical parameters:</b> Identical to the iCAM-MiniHD II BACK</p> <p><b>Camera parameters:</b> 2 Mpix 1080p, Day / Night, sensitivity: 0.05 Lux / F1.6 (color), 0.01 Lux / F1.6 (B / W), optical zoom x4, IR illuminator - NO, H264, lens adjustable: 2.8 - 12 mm motozoom, AWB, ATW, AGC, BLC, HLC, 3D DNR, DWDR,</p> <p><b>Observation range:</b> Events detection from a distance: 110 m, Observation: 45 m, Diagnosis: 22 m, Identification: 10 m.</p> <p><b>Working time on the battery:</b> up to 10h</p> <p><b>Includes:</b> iCAM-MiniHD II BACK, Hikvision camera x 1 pcs, SD128GB memory x 1 pcs, antennas, GE-Mobile II quick assembly socket x 1 pcs, mounting accessories x 1 pc.</p>	iCAM	€ 2 430,00

Price list of rapid deployment cameras PRO designed for city monitoring and City Guards/Police.

CAMSAT 2019

below prices anre netto and do not include VAT 23% tax valid since 01.04.2019

Group	Index	Model	Picture	Description and features	Technical parameters	Discount	Netto retail price
iCAM	1093	<b>iCAM-Mini II X15 Duplex DOME-4M</b>  (with camera PTZ and 2 fixed cameras Hikvision)		<p>POWER SUPPLY: WITH CONTINUOUS 230V AC POWER</p> <p><b>LTE rapid deployment video monitoring system with 230V emergency power supply for 4h</b></p> <p>It allows observation of a large area and a detailed analysis of selected places.</p> <p><b>Key features:</b>            * as in iCAM-MiniHD II BACK            * Camera - YES (2 fixed cameras 4 Mpix, IR 30 m, 1 PTZ camera 2 Mpix, x15, IR 100 m)            * Video recording for 7-10 days</p>	<p><b>Technical parameters:</b> Identical to the iCAM-MiniHD II BACK</p> <p><b>Parameters of the PTZ camera:</b> 2 Mpix 1080p, Day / Night, sensitivity: 0.005 Lux (color), 0.001 Lux (B / W), optical zoom x15, IR illuminator for 100 m, h265 +, lens: 5 ~ 75 mm, AWB, ATW , AGC, BLC, HLC, EIS, WDR 120 dB, 3D DNR, ROI, Defog, functions of intelligent image analysis: virtual line crossing, intrusion and detection, appearance / disappearance of the object.</p> <p><b>Parameters of fixed cameras:</b> 2x 4 megapixels 2560x1440p, Day / Night, sensitivity: 0.01 Lux (color), 0 Lux (B / W IR), optical zoom x4, IR illuminator for 30 m, H265 +, lens: 2.8 ~ 12 mm moto zoom , AWB, AGC, BLC, 3D DNR, WDR 120dB, ROI, motion detection.</p> <p><b>The range of the PTZ camera observation:</b> Event detection: from a distance of 900 m, Observation: 380 m, Diagnosis: 180 m, Identification: 90 m</p> <p><b>Working time on the battery:</b> up to 4 hours</p> <p><b>Includes:</b> iCAM-MiniHD II BACK, Hikvision PTZ camera x 1 pcs, Hikvision fixed camera x 2 pcs, SD128GB memory 3 x pcs, antennas, GE-Mobile II quick assembly socket x 1 pc., assembly accessories x 1 pc.</p>	iCAM	€ 2 930,00
iCAM	1094	<b>iCAM-Mini II Triplex DOME-4M</b>  (with 3 fixed cameras Hikvision)		<p>POWER SUPPLY: WITH CONTINUOUS 230V AC POWER</p> <p><b>LTE rapid deployment video monitoring system with 230V emergency power supply for 4h.</b> Designed for permanent observation of a wide terrain of 3x 90°.</p> <p><b>Key features:</b>            * as in iCAM-MiniHD II BACK            * Camera - YES (3 fixed cameras 4Mpix, IR30)            * Video recording for 5-7 days for 4Mpix and 7-10 days for 4Mpix</p>	<p><b>Technical parameters:</b> Identical to the iCAM-MiniHD II BACK</p> <p><b>Camera parameters:</b> 4Mpix 2560x1440p, Day / Night, sensitivity: 0.01 Lux (color), 0 Lux (B / W IR), optical zoom x4, IR illuminator at 30m, H265 +, lens: 2.8 ~ 12mm motor zoom, AWB, AGC, BLC, 3D DNR, WDR 120dB, ROI, motion detection.</p> <p><b>Observation range:</b> Events detection from a distance: 193 m, Observation: 77 m, Diagnosis: 39 m, Identification: 19 m</p> <p><b>Working time on the battery:</b> up to 4 hours</p> <p><b>Includes:</b> iCAM-MiniHD II BACK, Hikvision camera x 3 pcs, SD128GB memory x3 pcs, antennas, GE-Mobile II quick assembly socket x 1 piece, mounting accessories x1 pcs</p>	iCAM	€ 3 297,00
iCAM	1095	<b>iCAM-Mini II DOME-4M</b>  (with camera 2K-4Mpix Hikvision)		<p>POWER SUPPLY: WITH CONTINUOUS 230V AC POWER</p> <p><b>LTE rapid deployment video monitoring system with 230V emergency power supply for 4h.</b> Designed for permanent observation of terrain with an angle of 90° in very high resolution 2K (4Mpix - 2688 × 1520).</p> <p><b>Key features:</b>            * as in iCAM-MiniHD II BACK            * Camera - YES (4 Mpix camera, IR 50 m)            * Video recording for 5-7 days for 4 Mpix and 7-10 days for 2 Mpix</p>	<p><b>Technical parameters:</b> Identical to the iCAM-MiniHD II BACK</p> <p><b>Camera parameters:</b> 4 Mpix 2560x1440p, Day / Night, sensitivity: 0.01 Lux (color), 0 Lux (B / W IR), IR illuminator for 30 m, h265 ++, lens: 2.8-12 mm, AWB, ATW, AGC, BLC , HLC, EIS, WDR 120 dB, 3D DNR, ROI, motion detection.</p> <p><b>Observation range:</b> Event detection: from a distance of 193 m, Observation: 77 m, Diagnosis: 39 m, Identification: 19 m.</p> <p><b>Working time on the battery:</b> up to 4 hours</p> <p><b>Includes:</b> iCAM-MiniHD II BACK, Hikvision camera x 1 pcs, SD128GB memory x 1 pcs, antennas, GE-Mobile II quick assembly socket x 1 pcs, mounting accessories x 1 pc.</p>	iCAM	€ 2 093,00

Price list of rapid deployment cameras PRO designed for city monitoring and City Guards/Police.

CAMSAT 2019

below prices anre netto and do not include VAT 23% tax valid since 01.04.2019

Group	Index	Model	Picture	Description and features	Technical parameters	Discount	Netto retail price
<b>iCAM-MiniHD I</b>							
<b>Rapid deployment cameras 4G/LTE powered with DC 48V (24V)</b>							
<b>No camera - Main unit for any IP camera</b>							
iCAM	1123	<b>iCAM-MiniHD I BACK</b> (2019)  (compatible with Hikvision, Dahua,...)		<p>POWER SUPPLY: WITH CONTINUOUS POWER 48V DC</p> <p><b>LTE rapid deployment video monitoring system - miniature (without IP camera).</b></p> <p><b>Key features:</b></p> <ul style="list-style-type: none"> <li>* 4G / LTE - YES (2xSIM)</li> <li>* Battery - NO</li> <li>* Mobility and quick slide assembly - YES</li> <li>* Compatible with cameras and NVR Hikvision / Dahua - YES</li> <li>* Camera - NO (mechanically adapted to mount almost any PTZ IP camera of such brands as: Dahua, Hikvision ...)</li> </ul>	<p><b>The most important parameters:</b> 4G / LTE transmission, 2x SIM socket, 1x LAN port with PoE, 48V DC power supply, mechanical adapter for attaching a Dahua and Hikvision PTZ suspended camera, fast pole / wall mounting socket, IP66, does not include a camera.</p> <p><b>New parameters for version 2019:</b></p> <ul style="list-style-type: none"> <li>* The possibility of displaying in the OSD video image information about: alarm event, power status, GSM connection quality;</li> <li>* Possibility to install the option: "MASS EVENTS" - a tool that helps to make a smooth LTE transmission surrounded by thousands of mobile phones, eg near festivals, demonstrations, sports events, etc.</li> </ul> <p><b>Camera parameters:</b> does not contain a camera. Apply your own IP camera of any brand.</p> <p><b>Includes:</b> iCAM-MiniHD I BACK, antenna, quick assembly GE-Mobile II x 1 pcs. DC 48V power supply, mounting accessories x 1 pc.</p> <p><b>Recommended accessories:</b> Mounting adapter for cameras: Bosch, Axis, Avigillion, Novus, UNV, IDIS, Flir, GANZ and others; mounting adapter for horn cameras; LTE SIMcam card; remote controller; GPS; iCAM-BOX; Wi-Fi;</p> <p>In the case of delivery of an IP camera to CAMSAT, the product will be sent back fully operational and ready for work.</p>	ICAM	€ 993,00
<b>Full set - main unit with cameras</b>							
iCAM	1124	<b>iCAM-MiniHD I X4</b> (2019)  (with camera PTZ Hikvision)		<p>POWER SUPPLY: WITH CONTINUOUS POWER 48V DC</p> <p><b>LTE rapid deployment video monitoring system - miniature with PTZ camera</b></p> <p><b>Key features:</b></p> <ul style="list-style-type: none"> <li>* 4G / LTE - YES (2xSIM)</li> <li>* Battery - NO</li> <li>* Mobility and quick slide assembly - YES</li> <li>* Camera - YES (rotary PTZ, zoom x4)</li> </ul>	<p><b>The most important parameters:</b> Identical to the iCAM-MiniHD and BACK</p> <p><b>Camera parameters:</b> 2 Mpix 1080p, Day / Night, sensitivity: 0.05 Lux / F1.6 (color), 0.01 Lux / F1.6 (B / W), optical zoom x4, IR illuminator - NO, H264, lens adjustable: 2.8 - 12 mm motozoom, AWB, ATW, AGC, BLC, HLC, 3D DNR, DWDR,</p> <p><b>Observation range:</b> Event detection from a distance: 110 m, Observation: 45 m, Diagnosis: 22 m, Identification: 10 m.</p> <p><b>Includes:</b> iCAM-MiniHD I BACK, PTZx1 camera, antennas, GE-Mobile II quick assembly socket x 1 pcs, 48V DC power supply, mounting accessories x 1 pc.</p> <p><b>Recommended accessories:</b> Mounting adapter for cameras: Bosch, Axis, Avigillion, Novus, UNV, IDIS, Flir, GANZ and others; mounting adapter for horn cameras; LTE SIMcam card; remote controller; GPS; iCAM-BOX; transmission Wi-Fi;</p> <p>In the case of delivery of an IP camera to CAMSAT, the product will be sent back fully operational and ready for work.</p>	ICAM	€ 1 660,00

**Price list of rapid deployment cameras PRO designed for  
city monitoring and City Guards/Police.**

**CAMSAT 2019**

below prices anre netto and do not include VAT 23% tax  
valid since 01.04.2019

Group	Index	Model	Picture	Description and features	Technical parameters	Discount	Netto retail price
<b>ICAM-PowerHD</b> <b>Mobile 4G / LTE cameras for OPERATING tasks</b> <b>powered from a removable lithium battery with a capacity of 64 Ah</b>							
<b>No camera - Main unit for any IP camera</b>							
ICAM	1080	<b>iCAM-PowerHD BACK</b> (version 2019)  (compatible with Hikvision, Dahua, ...)		<b>POWER SUPPLY: 12V DC BATTERY</b>  <b>Rapid deployment LTE video monitoring system with its own high-capacity battery backup - without an IP camera</b> Designed for quick commissioning anywhere without a power source. For operational use for special services, military and everywhere where there is no power supply.  <b>Key features:</b> * 4G / LTE - YES (2xSIM) * Battery - YES (3 days) * Automatic charging of the battery with 230V - NO * Mobility and quick slide assembly - YES * Compatible with cameras and NVR Hikvision / Dahua - YES * Camera - NO (mechanically adapted to mount almost any PTZ IP camera of such brands as: Dahua, Hikvision ...)	<b>Technical parameters:</b> 4G / LTE transmission, SIM slot x 2 pcs, LAN port with PoE x 2 pcs, power supply: battery, 12V, 24V DC; Light, replaceable Li-Ion 64Ah battery; CAM-OFF and StandBy controlled by SMS, detecting disassembly with SMS notification, mechanical adapter for mounting any IP PTZ Hikvision and Dahua camera, quick sliding assembly, transparent for connection between camera and VMS, built-in battery charger - NO, external IP66.  <b>New parameters for version 2019:</b> * The possibility of displaying in the OSD video image information about: alarm event, battery status and voltage, charging, sabotage, GSM connection quality; * Possibility to install the option: "MASS EVENTS" - a tool that helps to make a smooth LTE transmission surrounded by thousands of mobile phones, eg near festivals, demonstrations, sports events, etc. <b>Camera parameters:</b> does not contain a camera. Use your own IP camera from any manufacturer.  <b>Working time on the battery depends on the power consumption of the IP camera [camera power]:</b> * <4W: up to 105h or up to 200h working with an additional iCAM-Battery * <8W: up to 72 hours or up to 144 hours of work with iCAM-Battery * <12W: up to 57h or up to 100h of work with iCAM-Battery * <18W: up to 42h or up to 80h working with iCAM-Battery  <b>Includes:</b> iCAM-PowerHD BACK, Li-Ion charger, antennas, GE-Mobile II quick-assembly socket x 1 pcs, mounting accessories x 1 pc.  <b>Recommended accessories:</b> Mounting adapter for cameras: Bosch, Axis, Avigillion, Novus, UNV, IDIS, Flir, GANZ and others; mounting adapter for horn cameras; LTE SIMcam card; RC remote control; GPS; iCAM-BOX; Wi-Fi;  In the case of delivery of an IP camera to CAMSAT, the product will be sent back fully operational and ready for work.	ICAM	€ 4 933,00
<b>Full set - main unit with cameras</b>							
ICAM	1081	<b>iCAM-PowerHD X4 LTE</b> (version 2019)  (with camera PTZ Hikvision)		<b>POWER SUPPLY: 12V DC BATTERY</b>  <b>Rapid deployment LTE video monitoring system with its own battery power supply with a large capacity for 3 days and with a PTZ camera.</b>  <b>Key features:</b> * as in iCAM-PowerHD BACK * Camera - YES (PTZ with zoom x4) * Video recording for 7-10 days	<b>Technical parameters:</b> same as in iCAM-PowerHD BACK <b>Camera parameters:</b> 2 Mpix 1080p, Day / Night, sensitivity: 0.05 Lux / F1.6 (color), 0.01 Lux / F1.6 (B / W), optical zoom x4, IR illuminator - NO, H264, lens adjustable: 2.8 - 12 mm motozoom, AWB, ATW, AGC, BLC, HLC, 3D DNR, DWDR, <b>Observation range:</b> Event detection from a distance: 110 m, Observation: 45 m, Diagnosis: 22 m, Identification: 10 m. <b>Working time:</b> up to 72 hours or up to 144 hours of work with an additional iCAM-Battery module <b>Includes:</b> iCAM-PowerHD BACK, Hikvision PTZ rotary camera, Li-Ion battery charger, SD128GB memory card, antennas, GE-Mobile II quick assembly socket x 1 pcs, mounting accessories x 1 pc.	ICAM	€ 5 300,00
ICAM	1082	<b>iCAM-PowerHD X30 IR150 LTE</b> (version 2019)  (with camera PTZ Dahua or Hikvision)		<b>POWER SUPPLY: 12V DC BATTERY</b>  <b>Mobile LTE video monitoring system with its own battery power supply with large capacity for 2 days</b>  <b>Key features:</b> * as in iCAM-PowerHD BACK * Camera - YES (PTZ with zoom x30, IR 150 m) * Video recording for 7-10 days	<b>Parameters:</b> identical as in iCAM-PowerHD BACK <b>Camera parameters:</b> PTZ camera, 2 Mpix, Day / Night, sensitivity: 0.005 Lux / F1.6 (color), 0.0005 Lux / F1.6 (B / W), optical zoom x30, IR illuminator for 150 m, h265 +, adjustable lens: 4.5 - 135mm, AWB, AGC, ATW, BLC, HLC, EIS, 2D / 3D DNR, WDR 120dB, Rol, Defog, intelligent image analysis (IVS) functions: Auto Tracking, virtual line crossing, intrusion detection, face detection and appearance / disappearance of the object, registration of the largest traffic (trace on the heat map). <b>Observation range:</b> Event detection: at a distance of 1862 m, Observation: 744 m, Diagnosis: 372 m, Identification: 186 m <b>Working time:</b> up to 24 hours or up to 48 hours of work with an additional iCAM-Battery module <b>Includes:</b> iCAM-PowerHD BACK, Dahua PTZ swivel camera, Li-Ion charger, SD128GB memory card, antennas, GE-Mobile II quick assembly socket x 1 pcs. Mounting accessories x 1 pc.	ICAM	€ 5 633,00

**Price list of rapid deployment cameras PRO designed for city monitoring and City Guards/Police.**

**CAMSAT 2019**

below prices anre netto and do not include VAT 23% tax  
valid since 01.04.2019

Group	Index	Model	Picture	Description and features	Technical parameters	Discount	Netto retail price
<b>Options</b>							
<b>extending the functionality of rapid deployment cameras</b>							
Opce iCAM iConstruction	1100	iCAM-Adapter Option 00 64		Option available with: * iConstruction-CAM * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II	<b>Mounting adapter for any cameras, eg Bosch, Novus, Axis, UNV, Avigilon, etc.</b> Adapter for mounting IP PTZ cameras with hanging pipe fitting. The set includes an adapter for mounting PTZ cameras of various brands. Ask the CAMSAT technical department for details and compatibility.	-	<b>Individual pricing. Depends on the camera model and brand</b>
	1101	RemoteControl Option 00 43		Option available with: * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD II	<b>Radio remote controller for iCAM systems</b> Radio remote control for remote turning off / on the camera with a range of 10 m. It allows to significantly extend the battery operation time by turning it off during the period of non-use. The option includes an RC remote control and a control module.	C	€ 227,00
	1102	iMount-Triplex Option 00 60		Option available with: * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD II	<b>Mounting adapter for up to three fixed cameras</b> The adapter allows the installation of three fixed cameras on devices from the iCAM series. Ask the CAMSAT technical department for details and compatibility.	C	€ 187,00
iCAM & iConstruction options	1103	iMount-Duplex Option 00 61		Option available with: * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD II	<b>Mounting adapter for 1 PTZ camera and 2 fixed cameras</b> The adapter allows the installation of 1 PTZ camera and 2 fixed cameras on the iCAM series devices. Ask the CAMSAT technical department for details and compatibility.	C	€ 187,00
	1104	GeoSecurity Option 00 29		Option available with: * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II	<b>Camera GPS geolocation with zone exit notification system</b> GPS geo location + SMS / Email notification system for disassembly or theft. The system allows you to inform the user, eg if the camera leaves the assembly zone (works via LTE).	C	€ 327,00
	1105	Lock Option 00 31		Option available with: * iConstruction-CAM * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II	<b>Lock, padlock to protect the camera from unauthorized disassembly</b>	C	€ 19,00
iCAM & iConstruction options	1106	StandBy Option 00 42		Option available with: * iCAM-PowerHD	<b>Standby mode activated by SMS</b> Special battery saving mode in the camera activated by SMS (extends the battery operation time significantly). The control is carried out by sending an order via SMS.	-	<b>individual pricing</b>
	1107	RALcolor Option 00 49		Option available with: * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II	<b>Selected Color iCAM</b> Selected special camera color according to RAL palette made in powder coating technology. Delivery time +14 days.	-	<b>individual pricing</b>
	1108	Wifi Option 00 24		Option available with: * iConstruction-CAM * iCAM-PowerHD * iCAM-MiniHD I i II	<b>WiFi with a range of 50 m working in the 2.4GHz band for iCAM and iConstruction systems</b> Wireless WiFi transmission for wireless system configuration. It enables: viewing, controlling, browsing and downloading the archive and system management.	C	€ 127,00
	1109	Rec2T Option 00 20		Option available with: * iCAM-MobileHD II	<b>Special 2T memory for the iCAM-MobileHD II mobile camera.</b> It provides continuous recording of HD video content up to 90 days of recordings.	C	€ 184,00

Price list of rapid deployment cameras PRO designed for city monitoring and City Guards/Police.

CAMSAT 2019

below prices are netto and do not include VAT 23% tax  
valid since 01.04.2019

Group	Index	Model	Picture	Description and features	Technical parameters	Discount	Netto retail price
<b>Accessories</b> for rapid deployment cameras							
iCAM & iConstruction options	1112	iCAM-Magnetic STAND NEW 2018/2019 Option 00 62		Compatible with: * iConstruction-CAM * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II	<b>Magnetic tripod for the roof of the car</b> A powerful magnetic tripod for mobile cameras from the iCAM and iConstruction series. A magnetic stand designed for mounting on the roof of a car.	iCAM	€ 1 153,00
	1113	iCAM-Battery Option 00 27		Compatible with: * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II * any camera IP PoE	<b>External battery module (LI-ION)</b> External, light battery IP66 adapted to supply mobile camera systems from the series: • iCAM-MobileHD II - increases the battery operation time by 200% (from 24-32h) • iCAM-PowerHD - increases the battery operation time by 100% (from 48 -140h) • iCAM-MiniHD - allows battery operation of the iCAM-MiniHD system for 24-72h continuous operation	iCAM	€ 1 660,00
	1114	iCAM-Battery230 Option 00 63		Compatible with: * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II * any camera IP PoE	<b>iCAM-Battery230 - External battery module (LI-ION) with automatic charging eg from a 230V lighting pole</b> An additional battery module that allows you to extend the work by 100% or the standard camera operation time x2 . In addition, it can be automatically charged from the 230V light pole in a very short time. Thanks to the iCAM-Battery230 module, we will receive the iCAM-MobileHD II mobile camera with continuous battery operation for 14-18 hours.	iCAM	€ 1 993,00
	1115	iCAM-BOX Option00 48		Compatible with: * iConstruction-CAM * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD II	<b>Strong transport box for mobile systems: iCAM and iConstruction with foam filling.</b> It enables safe transport and storage of mobile cameras. Dimensions: 60 x 50 x 35 cm	C	€ 427,00
	1116	Mounting socket GE-Mobile II Option 00 52		Compatible with: * iConstruction-CAM * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II	<b>The universal iCAM II rapid deployment camera quick connector socket. Can be screwed to the wall or attached with steel bands to the post 80-160 mm</b> Quick coupler socket for mounting a rapid deployment camera on a pole or façade. The installation of several such sockets in the city area enables very fast moving and installation of iCAM cameras in a new location.	C	€ 97,00
	1117	iCAM-TVRec Option 00 26		Compatible with: * iConstruction-CAM * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II	<b>Online HDMI receiver for 4 iCAM cameras</b> Receiver for viewing 4 images from iCAM cameras or iConstructionCAM on TV via the Internet. In addition, it allows you to record video images, control PTZ cameras, online preview in HD and many other options.  <b>Included:</b> iCAM-TVRec, power supply x 1 pcs	iCAM	€ 327,00

Price list of rapid deployment cameras PRO designed for city monitoring and City Guards/Police.

CAMSAT 2019

below prices are netto and do not include VAT 23% tax  
valid since 01.04.2019

Group	Index	Model	Picture	Description and features	Technical parameters	Discount	Netto retail price
iCAM & iConstruction options	1118	PTZ-Keyboard Option 00 50		Compatible with: * iConstruction-CAM * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II	Keyboard controlling the PTZ camera PTZ control keyboard with 3D joystick for iCAM cameras.	-	individual pricing
	1119	PTZ-Keyboard/Video Option 00 51		Compatible with: * iCAM-MobileHD II * iCAM-PowerHD * iCAM-MiniHD I i II	Keyboard controlling the PTZ camera with the Video preview PTZ control keyboard with 3D joystick for iCAM cameras with screen for video image preview.	-	individual pricing
	1120	iCAM-AKU22 Option 00 53		Compatible with: * iCAM-MobileHD II * iCAM-Battery230	A light LI-ION battery for powering the iCAM-MobileHD I and II system A special, light battery with up to 12-16h of working time and designed to work in temperatures below -30 ° C + 55 ° C. A specialized battery with the possibility of charging in minus temperatures -20 ° C + 55 ° C. Lifetime of over 5,000 charging cycles with a capacity drop of up to 80%. Quick-change battery in iCAM-MobileHD and iCAM-MobileHD II systems	C	€ 453,00
	1121	iCAM-AKU64 Option 00 54		Compatible with: * iCAM-PowerHD * iCAM-Battery	A light LI-ION battery for powering iCAM-PowerHD and iCAM-Battery. A special, light battery with up to 72h of working time and designed to work in temperatures -10° C to + 55° C. Charging temperature 0° C + 55° C. Quick-change battery in iCAM-PowerHD and iCAM-Battery systems.	C	€ 967,00
	1122	iCAM-Receiver Option 00 37		Compatible with: * iCAM-MobileHD II	Wireless radio receiver with LAN output A radio module for receiving a wireless signal from the iCAM system within a radius of 1km. It allows you to connect the signal from mobile cameras to your own LAN and receive images on any computer or NVR with ONVIF.	iCAM	€ 263,00