iCAM-TOWER	5MQ4	5MQ4 BACK	5MQ3	5MQ3 BACK	4MQ2	5MQ1	4MQ1	XXXX
Index number	6005	6005b	6004	6004b	6003	6002	6001	On request
Tower made of galvanized steel, with supports	●	●	●	●	●	●	●	●
Pole height 4m or 5m	5m	5m	5m	5m	4m	5m	4m	[ ]
Fixed-position cameras [amount]	4	-	4	-	3	-	-	[ ]
PTZ – rotary cameras [amount]	1	-	-	-	1	-	-	[ ]
AI – intelligent functions of human and vehicle recognition, on all images.	●	-	-	-	-	-	-	[ ]
NVR – local video recording for 60 days	●	-	●	-	-	-	-	[ ]
LTE/4G – live transmission	●	●	●	●	●	-	-	[ ]
Wi-Fi	●	●	●	●	●	-	-	[ ]
Radio link to connect with other towers	-	-	-	-	-	-	-	[ ]
PIR – motion sensors, with 12m range within 360° around the tower	●	●	-	-	-	-	-	[ ]
iWirelessPIR-500M – wireless motion sensor with a radio range of 500m NLOS / 1000m LOS. 12m / 120°. Detection causes the PTZ camera to run into the detection area.	-	-	-	-	-	-	-	[ ]
Megaphone to send voice messages directly from the operator and an automatically generated voice message when a tamper is detected.	●	●	-	-	-	-	-	[ ]
LED lighting – two 45W LED halogen lights turning on when a sabotage is detected	●	●	-	-	-	-	-	[ ]
Alarm with notification to the monitoring station in the SIA-IP, PUSH, SMS standard. Signals: low battery, opening the tower door, tilting / moving the tower, cutting overhang cables, tampering the electronics, detection from AI cameras.	●	●	●	●	●	-	-	[ ]
Powered from 100—230V AC and 12V DC	●	●	●	●	●	-	-	[ ]
200Ah battery expandable up to 600Ah	●	●	●	●	●	-	-	[ ]
Solar power supply all-year-round without the need to replace or recharge the batteries, even in winter. Quick mounting / dismounting on the tower by inserting it into the mechanical socket.	-	-	-	-	-	-	-	[ ]